

Amendments to the specification,

Marked version of the replacement paragraph(s)/section(s), pursuant to 37 CFR 1.121(b)(1)(ii):

Please replace [Para 3] with the following rewritten paragraph:

Computer Program Listing Appendix under Sec. 1.52(e): This application includes a transmittal under 37 C.F.R. Sec. 1.52(e) of a Computer Program Listing Appendix. The Appendix, which comprises text file(s) that are IBM®-PC machine and Microsoft® Windows Operating System compatible, includes the below-listed file(s). All of the material disclosed in the Computer Program Listing Appendix can be found at the U.S. Patent and Trademark Office archives and is hereby incorporated by reference into the present application.

Please replace [Para 10] with the following rewritten paragraph:

While it is possible for humans to compose meaningful programs in machine code, practically all software development today employs one or more of the available programming languages. The most widely used programming languages are the "high-level" languages, such as C++, Pascal, Java®, and C#®. These languages allow data structures and algorithms to be expressed in a style of writing that is easily read and understood by fellow programmers.

Please replace [Para 36] with the following rewritten paragraph:

Referring to the figures, exemplary embodiments of the invention will now be described. The following description will focus on the presently preferred embodiment of the present invention, which is implemented in desktop and/or server software (e.g., driver, application, or the like) operating in an Internet-connected environment running under an operating system, such as the Microsoft Windows® operating system. The present invention, however, is not limited to any one particular application or any particular environment. Instead, those skilled in the art will find that the system and methods of the present invention may be advantageously embodied on a variety of different platforms, including Macintosh®, Linux®, Solaris™, UNIX®, FreeBSD®, and the like. Therefore, the description of the exemplary embodiments that follows is for

purposes of illustration and not limitation. The exemplary embodiments are primarily described with reference to block diagrams or flowcharts. As to the flowcharts, each block within the flowcharts represents both a method step and an apparatus element for performing the method step. Depending upon the implementation, the corresponding apparatus element may be configured in hardware, software, firmware or combinations thereof.

Please replace [Para 39] with the following rewritten paragraph:

CPU 101 comprises a processor of the Intel Pentium® family of microprocessors. However, any other suitable processor may be utilized for implementing the present invention. The CPU 101 communicates with other components of the system via a bi-directional system bus (including any necessary input/output (I/O) controller circuitry and other "glue" logic). The bus, which includes address lines for addressing system memory, provides data transfer between and among the various components. Description of Pentium-class microprocessors and their instruction set, bus architecture, and control lines is available from Intel Corporation of Santa Clara, CA. Random-access memory 102 serves as the working memory for the CPU 101. In a typical configuration, RAM of sixty-four megabytes or more is employed. More or less memory may be used without departing from the scope of the present invention. The read-only memory (ROM) 103 contains the basic input/output system code (BIOS) -- a set of low-level routines in the ROM that application programs and the operating systems can use to interact with the hardware, including reading characters from the keyboard, outputting characters to printers, and so forth.

Please replace [Para 47] with the following rewritten paragraph:

Software system 200 includes a graphical user interface (GUI) 215, for receiving user commands and data in a graphical (e.g., "point-and-click") fashion. These inputs, in turn, may be acted upon by the system 100 in accordance with instructions from operating system 210, and/or client application module(s) 201. The GUI 215 also serves to display the results of operation from the OS 210 and application(s) 201, whereupon the user may supply additional inputs or terminate the session. Typically, the OS 210

operates in conjunction with device drivers 220 (e.g., "Winsock" driver -- Windows' implementation of a TCP/IP stack) and the system BIOS microcode 230 (i.e., ROM-based microcode), particularly when interfacing with peripheral devices. OS 210 can be provided by a conventional operating system, such as Microsoft® Windows 9x, Microsoft® Windows NT, Microsoft® Windows 2000, or Microsoft® Windows XP, all available from Microsoft Corporation of Redmond, WA. Alternatively, OS 210 can also be an alternative operating system, such as the previously mentioned operating systems.